



HILMAN BULL DOLLY



Lightweight
Cost Effective
Solution for
Moving the Heavyweights

NEW!



Individual Bull Dolly Capacities

1-ton
3-ton
6-ton

Bull Dolly Kits Capacities

4-ton
12-ton
24-ton




HILMAN BULL DOLLY


Individual

Dollies


Rigid Diamond




Swivel Padded



Swivel Diamond



Swivel Smooth



Product Number	Roller Capacity	Top Style Description	Roller Material	Height inches mm	Width inches mm	Length inches mm	Weight lbs. kgs.
BRD-1N	1 ton	Rigid Diamond	Nylon	4.00 102	4.43 113	6.5 165	9 4
BRD-1P	1 ton	Rigid Diamond	Polyurethane	4.00 102	4.43 113	6.5 165	9 4
BRD-1S	1 ton	Rigid Diamond	Steel	4.00 102	4.43 113	6.5 165	9 4
BSP-1N	1 ton	Swivel Padded	Nylon	4.99 127	4.43 113	6.5 165	12 5
BSP-1P	1 ton	Swivel Padded	Polyurethane	4.99 127	4.43 113	6.5 165	12 5
BSP-1S	1 ton	Swivel Padded	Steel	4.99 127	4.43 113	6.5 165	12 5
BSD-1N	1 ton	Swivel Diamond	Nylon	4.43 113	4.43 113	6.5 165	11 5
BSD-1P	1 ton	Swivel Diamond	Polyurethane	4.43 113	4.43 113	6.5 165	11 5
BSD-1S	1 ton	Swivel Diamond	Steel	4.43 113	4.43 113	6.5 165	11 5
BRD-3N	3 ton	Rigid Diamond	Nylon	4.36 111	5.23 133	8.0 203	13 6
BRD-3P	3 ton	Rigid Diamond	Polyurethane	4.36 111	5.23 133	8.0 203	13 6
BRD-3S	3 ton	Rigid Diamond	Steel	4.36 111	5.23 133	8.0 203	13 6
BSP-3N	3 ton	Swivel Padded	Nylon	5.35 136	5.23 133	8.0 203	15 7
BSP-3P	3 ton	Swivel Padded	Polyurethane	5.35 136	5.23 133	8.0 203	15 7
BSP-3S	3 ton	Swivel Padded	Steel	5.35 136	5.23 133	8.0 203	15 7
BSD-3N	3 ton	Swivel Diamond	Nylon	4.79 122	5.23 133	8.0 203	16 7
BSD-3P	3 ton	Swivel Diamond	Polyurethane	4.79 122	5.23 133	8.0 203	16 7
BSD-3S	3 ton	Swivel Diamond	Steel	4.79 122	5.23 133	8.0 203	16 7
BSS-3N	3 ton	Swivel Smooth	Nylon	4.79 122	5.23 133	8.0 203	16 7
BSS-3P	3 ton	Swivel Smooth	Polyurethane	4.79 122	5.23 133	8.0 203	16 7
BSS-3S	3 ton	Swivel Smooth	Steel	4.79 122	5.23 133	8.0 203	16 7
BRD-6N	6 ton	Rigid Diamond	Nylon	4.45 113	10.0 254	11.0 279	34 15
BRD-6P	6 ton	Rigid Diamond	Polyurethane	4.45 113	10.0 254	11.0 279	34 15
BRD-6S	6 ton	Rigid Diamond	Steel	4.45 113	10.0 254	11.0 279	34 15
BSP-6N	6 ton	Swivel Padded	Nylon	6.60 142	10.0 254	11.0 279	39 18
BSP-6P	6 ton	Swivel Padded	Polyurethane	6.60 142	10.0 254	11.0 279	39 18
BSP-6S	6 ton	Swivel Padded	Steel	6.60 142	10.0 254	11.0 279	39 18
BSD-6N	6 ton	Swivel Diamond	Nylon	5.10 129	10.0 254	11.0 279	39 18
BSD-6P	6 ton	Swivel Diamond	Polyurethane	5.10 129	10.0 254	11.0 279	39 18
BSD-6S	6 ton	Swivel Diamond	Steel	5.10 129	10.0 254	11.0 279	39 18
BSS-6N	6 ton	Swivel Smooth	Nylon	4.85 123	10.0 254	11.0 279	38 17
BSS-6P	6 ton	Swivel Smooth	Polyurethane	4.85 123	10.0 254	11.0 279	38 17
BSS-6S	6 ton	Swivel Smooth	Steel	4.85 123	10.0 254	11.0 279	38 17

Note: All Swivel Top Styles Include Locks

We designed the Bull Dolly to be a lightweight, cost effective solution for moving heavy equipment. Anything such as large safes, chillers, condensers and machinery can be moved safely and effectively. Special nylon wheels are designed to resist marring your floors and combined with the turntable, to accommodate any turns that you require. A lock enables the units to be used as swivel or rigid top dollies. A "diamond" style top plate ensures a non-slip surface, though a neoprene pad should be utilized in addition.

Individual Bull Dollies are offered with capacities of 1-ton, 3-tons and 6-tons. Prepackaged Bull Dolly Kits are offered with capacities of 4-ton, 12-ton and 24-ton capacity. All prepackaged Kits include (4) Bull Dollies, (2) Steering Handles and (1) Storage Case.

KBRD-4N



KBSS-12S



KBSP-24P



Product Number	Kit Capacity	Dolly Capacity	Top Style Description	Roller Material	Kits Include			Weight	
								lbs.	kgs.
KBRD-4N	4 ton	1 ton	Rigid Diamond	Nylon	(4) BRD-1N Dollies	(2) Handles	(4) Pre-load pads	75	34
KBRD-4P	4 ton	1 ton	Rigid Diamond	Polyurethane	(4) BRD-1P Dollies	(2) Handles	(4) Pre-load pads	75	34
KBRD-4S	4 ton	1 ton	Rigid Diamond	Steel	(4) BRD-1S Dollies	(2) Handles	(4) Pre-load pads	75	34
KBSP-4N	4 ton	1 ton	Swivel Padded	Nylon	(4) BSP-1N Dollies	(2) Handles		85	39
KBSP-4P	4 ton	1 ton	Swivel Padded	Polyurethane	(4) BSP-1P Dollies	(2) Handles		85	39
KBSP-4S	4 ton	1 ton	Swivel Padded	Steel	(4) BSP-1S Dollies	(2) Handles		85	39
KBSD-4N	4 ton	1 ton	Swivel Diamond	Nylon	(4) BSD-1N Dollies	(2) Handles	(4) Pre-load pads	83	38
KBSD-4P	4 ton	1 ton	Swivel Diamond	Polyurethane	(4) BSD-1P Dollies	(2) Handles	(4) Pre-load pads	83	38
KBSD-4S	4 ton	1 ton	Swivel Diamond	Steel	(4) BSD-1S Dollies	(2) Handles	(4) Pre-load pads	83	38
<hr/>									
KBRD-12N	12 ton	3 ton	Rigid Diamond	Nylon	(4) BRD-3N Dollies	(2) Handles	(4) Pre-load pads	91	41
KBRD-12P	12 ton	3 ton	Rigid Diamond	Polyurethane	(4) BRD-3P Dollies	(2) Handles	(4) Pre-load pads	91	41
KBRD-12S	12 ton	3 ton	Rigid Diamond	Steel	(4) BRD-3S Dollies	(2) Handles	(4) Pre-load pads	91	41
KBSP-12N	12 ton	3 ton	Swivel Padded	Nylon	(4) BSP-3N Dollies	(2) Handles		100	45
KBSP-12P	12 ton	3 ton	Swivel Padded	Polyurethane	(4) BSP-3P Dollies	(2) Handles		100	45
KBSP-12S	12 ton	3 ton	Swivel Padded	Steel	(4) BSP-3S Dollies	(2) Handles		100	45
KBSD-12N	12 ton	3 ton	Swivel Diamond	Nylon	(4) BSD-3N Dollies	(2) Handles	(4) Pre-load pads	102	46
KBSD-12P	12 ton	3 ton	Swivel Diamond	Polyurethane	(4) BSD-3P Dollies	(2) Handles	(4) Pre-load pads	102	46
KBSD-12S	12 ton	3 ton	Swivel Diamond	Steel	(4) BSD-3S Dollies	(2) Handles	(4) Pre-load pads	102	46
KBSS-12N	12 ton	3 ton	Swivel Smooth	Nylon	(4) BSS-3N Dollies	(2) Handles		102	46
KBSS-12P	12 ton	3 ton	Swivel Smooth	Polyurethane	(4) BSS-3P Dollies	(2) Handles		102	46
KBSS-12S	12 ton	3 ton	Swivel Smooth	Steel	(4) BSS-3S Dollies	(2) Handles		102	46
<hr/>									
KBRD-24N	24 ton	6 ton	Rigid Diamond	Nylon	(4) BRD-6N Dollies	(2) Handles	(4) Pre-load pads	196	89
KBRD-24P	24 ton	6 ton	Rigid Diamond	Polyurethane	(4) BRD-6P Dollies	(2) Handles	(4) Pre-load pads	196	89
KBRD-24S	24 ton	6 ton	Rigid Diamond	Steel	(4) BRD-6S Dollies	(2) Handles	(4) Pre-load pads	196	89
KBSP-24N	24 ton	6 ton	Swivel Padded	Nylon	(4) BSP-6N Dollies	(2) Handles		216	98
KBSP-24P	24 ton	6 ton	Swivel Padded	Polyurethane	(4) BSP-6P Dollies	(2) Handles		216	98
KBSP-24S	24 ton	6 ton	Swivel Padded	Steel	(4) BSP-6S Dollies	(2) Handles		216	98
KBSD-24N	24 ton	6 ton	Swivel Diamond	Nylon	(4) BSD-6N Dollies	(2) Handles	(4) Pre-load pads	216	98
KBSD-24P	24 ton	6 ton	Swivel Diamond	Polyurethane	(4) BSD-6P Dollies	(2) Handles	(4) Pre-load pads	216	98
KBSD-24S	24 ton	6 ton	Swivel Diamond	Steel	(4) BSD-6S Dollies	(2) Handles	(4) Pre-load pads	216	98
KBSS-24N	24 ton	6 ton	Swivel Smooth	Nylon	(4) BSS-6N Dollies	(2) Handles		213	97
KBSS-24P	24 ton	6 ton	Swivel Smooth	Polyurethane	(4) BSS-6P Dollies	(2) Handles		213	97
KBSS-24S	24 ton	6 ton	Swivel Smooth	Steel	(4) BSS-6S Dollies	(2) Handles		213	97



HILMAN BULL DOLLY Kits



HILMAN BULL DOLLY



Wheel Option:
Nylon



Wheel Option:
Poly



Wheel Option:
Steel

Top Style:
Rigid
Diamond



Top Style:
Swivel
Diamond



Top Style:
Swivel
Padded



Top Style:
Swivel
Smooth



HILMAN WARRANTY

We warrant each new Bull Dolly sold by us to be free from manufacturing defects in normal service for a period of one (1) year commencing with delivery of the dolly to the original user. Our obligation under this warranty is expressly limited at our option, to the replacement or repair at Hilman Rollers, Marlboro, New Jersey 07746 USA, or at a service facility designated by us, of such part or parts as inspection shall disclose to have been defective. This warranty does not apply to defects caused by damage or unreasonable use, including failure to provide reasonable and necessary maintenance, while in the possession of the consumer.

WE SHALL NOT BE LIABLE FOR CONSEQUENTIAL DAMAGES OF ANY KIND, including, but not limited to, consequential labor costs or transportation charges in connection with the replacement or repair of defective parts. We make no warranty with respect to trade accessories. They are subject to the warranties of their manufacturers.

THERE ARE NO WARRANTIES EXCEPT AS ABOVE STATED. HILMAN DISCLAIMS AND EXCLUDES ANY IMPLIED WARRANTY OF MERCHANTABILITY OF ITS GOODS OR WARRANTY OF THE FITNESS OF THOSE GOODS FOR ANY PURPOSE OR USE. Subject to the express one-year warranty provided for the repair or replacement of defective goods, the customer acknowledges that it makes its purchase in reliance upon customers' inspection of the goods purchased from Hilman and not by reason of any representations made by or on behalf of Hilman.

We make no other express warranty, nor is anyone authorized to make any on our behalf. Any and all claims arising against Hilman Rollers or subsidiaries or affiliated firms concerning the use of the Hilman Rollers shall be governed by the laws of the State of New Jersey in the USA.



The specifications in this catalog are given as general information only and are not binding. Hilman reserves the right to change specifications or make alterations to products, parts or accessory equipment at any time without prior notice and for any reason whatsoever. All capacities are in metric tons

CONTACT INFORMATION

telephone..... (732) 462-6277

fax..... (732) 462-6355

toll free..... 1-888-2-ROLL-IT (N. America)

int'l fax..... (732) 462-3238

e-mail..... sales@hilmanrollers.com

address..... 12 Timber Lane
Marlboro NJ 07746 • USA

website..... www.hilmanrollers.com

ISO 9001
CERTIFIED

